

HI-TACK STATIC CLING



XCEL IS PLEASED TO OFFER THE BEST STATIC CLING AVAILABLE

Time and time again, customers prefer static cling from XCEL as it's made to order ensuring a fresh product. Fresh static cling reduces mottling, improves ink adhesion and provides superior window adhesion properties. XCEL offers the highest quality materials and utilizes specialized converting equipment so you can create a premium product and keep your customers happy and coming back for more.

TYPICAL APPLICATIONS

- Window Decals and Graphics
- Learning Tools and Game Pieces
- Promotional and Temporary Displays
- Protective Film
- Indoor P.O.P. Graphics



PRODUCT SPECIFICATIONS

Standard Gauges <i>(Custom gauges available)</i>	6-mil & 8-mil
Standard Widths <i>(Custom widths available)</i>	40" , 50" & 54"
Standard Colors <i>(Custom tints available)</i>	Clear & White
Surface Energy	32-36 dyne/cm
Minimum Application Temperature / Service Temperature	40° F / 0° F - 175° F
Dimensional Stability <i>(at 100° C)</i>	>8%
Tensile Strength <i>(MD/TD)</i>	2300 min. / 2200 min.
Gloss Level	150 +/- 25
Light Transmission / Haze <i>(Clear Only)</i>	~90% / ~10%
Liner Options <i>(Widths of each option will vary)</i>	70#, 8-pt & 10-pt

INK/PRINTER TECHNOLOGY

	Eco-Solvent Inkjet	Solvent Inkjet	Aqueous Inkjet	UV-Cured Inkjet	UV-Cured Litho/Offset	UV-Cured Screen	Latex Inkjet	Indigo Digital	Conventional Litho/Offset	Conventional Screen	Thermal	Rolls	Sheets
Hi-Tack Static Cling	●	●		●	●	●	○		○	○		●	●

Compatible	●	Not Qualified - Testing Required	○	Top Coated Version Required	T
------------	---	----------------------------------	---	-----------------------------	---

Xcel Products, Inc. does not represent, warrant or guarantee that all inks will adhere to Hi-Tack Static Cling. Xcel recommends testing the product for all intended applications and print technologies.

VISIT OUR NEW WEBSITE
xcelproducts.com

GIVE US A CALL!
(763) 231-3040
sales@xcelproducts.com

